

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 1

SECTION 1

PRODUCT IDENTIFIER HD 5700 EVERMORE INT ALK FLAT WH
DATE OF PREPARATION FEBRUARY 4, 2004
PRODUCT USE PROTECTIVE COATING

MANUFACTURED BY: ICI PAINTS NORTH AMERICA, 925 EUCLID AVENUE,
CLEVELAND, OHIO 44115, U.S.A.
ICI PAINTS (CANADA), 8200 KEELE STREET,
CONCORD, ONTARIO L4K 2A5, CANADA.

EMERGENCY AND MSDS TELEPHONE NUMBER:
1-800-545-2643

MSDS PREPARED BY: PRODUCT SAFETY AND TOXICOLOGY DEPARTMENT
ICI PAINTS NORTH AMERICA

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

	INGREDIENT	WT. %:
CHEMICAL NAME	LIMESTONE	40-50
COMMON NAME :	LIMESTONE	
CAS NUMBER:	1317-65-3	
CHEMICAL NAME	TITANIUM OXIDE	10-20
COMMON NAME :	TITANIUM DIOXIDE	
CAS NUMBER:	13463-67-7	
CHEMICAL NAME	HEXANOIC ACID, 2-ETHYL-, COBALT(2+) SALT	.1-1.0
COMMON NAME :	COBALT ALKANOATE	
CAS NUMBER:	136-52-7	
CHEMICAL NAME	CERAMIC MATERIALS AND WARES, CHEMICALS	10-20
COMMON NAME :	CALCINED KAOLIN CLAY	
CAS NUMBER:	66402-68-4	
CHEMICAL NAME	SOYBEAN OIL, POLYMER WITH ETHYLENE GLYCOL, FUMARIC PENTAERYTHRITOL AND PHTHALIC ANHYDRIDE	10-20
COMMON NAME :	ALKYD RESIN, SOYBEAN OIL	
CAS NUMBER:	68015-15-6	

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 2

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	DISTILLATES (PETROLEUM), STEAM-CRACKED, POLYMERS WITH LIGHT STEAM-CRACKED PETROLEUM NAPHTHA	1-5
COMMON NAME :	AROMATIC HYDROCARBON RESIN	
CAS NUMBER:	68410-16-2	
CHEMICAL NAME	WATER	5-10
COMMON NAME :	WATER	
CAS NUMBER:	7732-18-5	
CHEMICAL NAME	SOYBEAN OIL	1-5
COMMON NAME :	SOYA OIL, CRUDE	
CAS NUMBER:	8001-22-7	
CHEMICAL NAME	STODDARD SOLVENT	10-20
COMMON NAME :	MINERAL SPIRITS	
CAS NUMBER:	8052-41-3	

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE
INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

EFFECTS OF OVEREXPOSURE

INHALATION PROLONGED INHALATION MAY LEAD TO DIZZINESS AND/OR
LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING,
CHEST PAIN, COUGHING, CENTRAL NERVOUS SYSTEM DEPRESSION,
DIFFICULTY OF BREATHING, ALLERGIC RESPONSE, ASTHMATIC
REACTION, LIVER DAMAGE, KIDNEY DAMAGE, PNEUMOCONIOSIS, LOSS
OF CONSCIOUSNESS. POSSIBLE SENSITIZATION TO RESPIRATORY
TRACT.

SKIN CONTACT IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE
DERMATITIS, DEFATTING.

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 3

SECTION 3: HAZARDS IDENTIFICATION

EYE CONTACT IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, TEARING OF EYES, REDNESS OF EYES.

INGESTION INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, MOUTH AND THROAT IRRITATION, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, GASTRO-INTESTINAL DISTURBANCES, ABDOMINAL PAIN, CENTRAL NERVOUS SYSTEM DEPRESSION, DIFFICULTY OF BREATHING, CONVULSIONS, LOSS OF CONSCIOUSNESS.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
EYE, SKIN, RESPIRATORY DISORDERS, RESPIRATORY DISORDERS.

SECTION 4: FIRST-AID MEASURES

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING.
GET EMERGENCY MEDICAL ATTENTION.
HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.
REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING, HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.

SKIN CONTACT WASH THOROUGHLY WITH SOAP AND WATER. IF ANY PRODUCT REMAINS, GENTLY RUB PETROLEUM JELLY, VEGETABLE OR MINERAL/BABY OIL ONTO SKIN. REPEATED APPLICATIONS MAY BE NEEDED. REMOVE CONTAMINATED CLOTHING.
WASH CONTAMINATED CLOTHING BEFORE RE-USE.
DISPOSE OF CONTAMINATED LEATHER ITEMS, SUCH AS SHOES AND BELTS.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 4

SECTION 4: FIRST-AID MEASURES

INGESTION IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA) 105 F./ 41 C. LOWER EXPLOSIVE LIMIT .7 (%)
UPPER EXPLOSIVE LIMIT NOT AVAILABLE

FIRE EXTINGUISHING MEDIA
DRY CHEMICAL OR FOAM
WATER FOG.
CARBON DIOXIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.
VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.
MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.
RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS MATERIAL MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED.
IMMEDIATELY AFTER USE, PLACE SOAKED RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

FIRE FIGHTING PROCEDURES
WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.
FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS
CARBON MONOXIDE, CARBON DIOXIDE.
OXIDES OF CALCIUM.

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 5

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.

ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER.

LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.

SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE

STORE BELOW 100F (38C). KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP FROM FREEZING.

OTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.

KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE. GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION OF STATIC CHARGE.

AVOID SPONTANEOUS COMBUSTION OF CONTAMINATED RAGS AND OTHER EASILY IGNITABLE ORGANIC ACCUMULATIONS.

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 6

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME :	LIMESTONE			
CAS NUMBER:	1317-65-3			
ACGIH (TWA) :	10	MG/M3	OSHA (TWA) :	5 MG/M3
COMMON NAME :	TITANIUM DIOXIDE			
CAS NUMBER:	13463-67-7			
ACGIH (TWA) :	10	MG/M3	OSHA (TWA) :	10 MG/M3
COMMON NAME :	COBALT ALKANOATE			
CAS NUMBER:	136-52-7			
ACGIH (TWA) :	.02	MG/M3	OSHA (TWA) :	.05 MG/M3
COMMON NAME :	MINERAL SPIRITS			
CAS NUMBER:	8052-41-3			
ACGIH (TWA) :	100	PPM	OSHA (TWA) :	500 PPM

RESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.
USE EXPLOSION-PROOF EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT

EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING.

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 7

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	1.667
BOILING RANGE (F/C):	212-374/100-190	WEIGHT PER GALLON:	13.89/ 16.68IMP
%VOLATILE BY VOLUME:	38.47		
PHYSICAL STATE:	LIQUID	APPEARANCE	WHITE
SOLUBILITY IN WATER:	NOT AVAILABLE	PH:	NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS

STABLE

SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID

OXIDIZERS, ACIDS, BASES.

CONDITIONS TO AVOID

ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT,
FREEZING, SPARKS, OPEN FLAME, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : LIMESTONE

CAS NUMBER: 1317-65-3

CARCINOGENICITY LISTED BY: NTP NO

IARC NO

OSHA NO

ACGIH NO

LD50: 6450.00 MG/KG ORL RAT

COMMON NAME : TITANIUM DIOXIDE

CAS NUMBER: 13463-67-7

CARCINOGENICITY LISTED BY: NTP NO

IARC NO

OSHA NO

ACGIH NO

LD50: 24.00 GM/KG ORL RAT

LC50: 6820.00 MG/M3/4HR IHL RAT

COMMON NAME : COBALT ALKANOATE

CAS NUMBER: 136-52-7

CARCINOGENICITY LISTED BY: NTP NO

IARC NO

OSHA NO

ACGIH NO

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 8

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : CALCINED KAOLIN CLAY

CAS NUMBER: 66402-68-4

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : ALKYD RESIN, SOYBEAN OIL

CAS NUMBER: 68015-15-6

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : AROMATIC HYDROCARBON RESIN

CAS NUMBER: 68410-16-2

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : SOYA OIL, CRUDE

CAS NUMBER: 8001-22-7

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : MINERAL SPIRITS

CAS NUMBER: 8052-41-3

CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO

LD50:> 3.00 GM/KG SKN RBT

LD50:> 5.00 GM/KG ORL RAT

SUPPLEMENTAL HEALTH INFORMATION

NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

CARCINOGENICITY

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED COBALT AND CERTAIN COBALT COMPOUNDS AS POSSIBLY CARCINOGENIC TO HUMANS (GROUP 2B). INJECTION OF METALLIC COBALT, COBALT ALLOYS, AND CERTAIN COBALT COMPOUNDS HAS RESULTED IN THE DEVELOPMENT OF LOCALIZED TUMORS IN LABORATORY ANIMALS.

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 9

SECTION 11: TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS

NO REPRODUCTIVE EFFECTS ARE ANTICIPATED

MUTAGENICITY

NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY

NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY ICI PAINTS ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.
AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT

PAINT, COMBUSTIBLE LIQUID, UN 1263, PGIII

IMDG

NOT AVAILABLE

IATA

NOT AVAILABLE

TDG

NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

SARA	SARA	CERCLA	HAZ AIR	MARINE
302	313	302.4	POLLUTANT	POLTNT

CAS NUMBER:

136-52-7

NO

YES

NO

YES

NO

COMMON NAME :

COBALT ALKANOATE

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS

MATERIAL SAFETY DATA SHEET



925 EUCLID AVENUE
CLEVELAND, OHIO 44115
EMERGENCY TELEPHONE 1-800-545-2643

The information contained herein is based on data available at the time of preparation of this data sheet and which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

COMPLIES WITH OSHA HAZARD COMMUNICATIONS STANDARD 29CFR1910.1200.

HD 5700

PAGE 10

SECTION 15: REGULATORY INFORMATION

PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING)
ON THE TSCA INVENTORY.

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE
HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS)
AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE
CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE
AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH ICI
PAINTS BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS
EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA.
ICI PAINTS SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS
INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS
MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS
SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE
PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF
YOUR EMPLOYEES AND USERS OF THIS MATERIAL.
COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD
29CFR1910.1200.